

BLANK PAGE



Indian Standard

SPECIFICATION FOR WASHERS FOR USE WITH FITTINGS FOR WATER SERVICES

(First Revision)

First Reprint MAY 1990

UDC 621.646.6-762:696.14

© Copyright 1983

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

SPECIFICATION FOR WASHERS FOR USE WITH FITTINGS FOR WATER SERVICES

(First Revision)

Sanitary Appliances and Water Fittings Sectional Committee, BDC 3

Chairman

Representing

SHRI K. D. MULEKAR

Municipal Corporation of Greater Bombay

Members

DY HYDRAULIC ENGINEER (Alternate to

Shri K. D. Mulekar) Adviser (PHE)

Central Public Health & Environmental Engineering Organization (Ministry of Works & Housing).

New Delhi DEPUTY ADVISER (PHE) (Alternate)

SHRI M. K. BASU

Central Glass & Ceramic Research Institute (CSIR),

SERY D. S. CHARHAL.

Directorate General of Technical Development, New Delhi

SHRI T. RAMASUBRAMANIAN (Alternate)

SHRI S. P. CHAKRABARTI

Central Building Research Institute, Roorkee

SHRI S. K. SHARMA (Alternate)

CHIEF ENGINEER

Public Health Engineering Department, Government of Kerala

SHRIK. RAMACHANDRAN (Alternate)

CHIEF ENGINEER

Uttar Pradesh Jal Nigam, Lucknow

SUPERINTENDING ENGINEER (Alternate)

SHRI J. D'CRUZ

Delhi Municipal Corporation ADDL CHIEF ENGINEER (Alternate)

DIRECTOR SHRI B. R. N. GUPTA Bombay Potteries & Tiles Ltd, Bombay Engineer-in-Chief's Branch, Army Headquarters, New

Delhi

SHRI K. V. KRISHNAMURTHY (Alternate)

SHRIP. J'GANATH RAO EID Parry Ltd, Ranipet

SHRI M. MOOSA SULAIMAN (Alternate)

National Environmental Engineering Seri S. R. Kshirsagar Research Institute (CSIR), Nagpur

SHRI R. C. REDDY (Alternate)

(Continued on page 2)

(c) Copyright 1983

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the oublisher shall be deemed to be an infringement of copyright under the said Act.

18:4346-1982

(Continued from page 1)

Members Representing SHRIK, LAKSHMINARAYANAN Hindustan Shipyard Ltd, Vishakhapatnam SHRI A. SHARIFF (Alternate) SHRIE, K. RAMACHANDRAN National Test House, Calcutta SHRI S. K. BANEBJER (Alternate) Railway Board (Ministry of Railways) SHRI RANJIT SINGH National Buildings Organization, New Delhi DB A. V. R. R'AO SHRI J. SENGUPTA (Alternate) SHRI R. K. SOMANY Hindustan Sanitaryware & Industries Ltd, Bahadurgarh (Haryana) SHRI R. K. SUNDRAM Central Public Works Department Works I SURVEYOR OF (NDZ) (Aliernate) SHRI T. N. UBOVEJA Directorate General of Supplies & Disposals, New Delhi SHRIG, RAMAN. Director General, ISI (Ex-officio Member)

Secretary

SHRI C. K. BEBARTA Deputy Director (Civ Engg), ISI

Domestic and Municipal Water Fittings Subcommittee, BDC 3:2

Convener

Director (Civ Engg)

SHRI K. D. MULEKAR

Municipal Corporation of Greater Bombay

Members

DEPUTY HYDRAULIC ENGINEER (Alternate to

Shri K. D. Mulekar)

SHRI YASH RAJ AGGARWAL Goverdhan Das P. A., Calcutta

Raj JOGINDER

AGGARWAL (Alternate)

Bangalore Water Supply & Sewerage Board, CHIEF ENGINEER

Bangalore

Tamil Nadu Water Supply & Drainage Board, CHIEF ENGINEER

Madras Uttar Pradesh, Jal Nigam, Lucknow CHIEF ENGINEER

SUPERINTENDING ENGINEER (Alternate)

Municipal Corporation of Delhi, Delhi SHRI J. D'CRUZ

SARI S. A. SWAMY (Alternate)

Maharashtra Engineering Research Institute, Nasik RESEARCH OFFICER (Alternate)

SHRIB. R. N. GUPTA Engineer-in-Chiefs Branch (Ministry of Defence), New Delhi

SHRIK. V. KRISHNAMURTHY (Alternate)

Hind Trading & Manufacturing Co Limited, New SHRI M. K. JAIN

Delhi

SHEI K. K. JAIN (Alternate)

(Continued on page 7

Indian Standard SPECIFICATION FOR WASHERS FOR USE WITH FITTINGS FOR WATER SERVICES

(First Revision)

O. FOREWORD

- **0.1** This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 30 November 1982, after the draft final zed by the Sanitary Appliances and Water Fittings Sectional Committee had been approved by the Civil Engineering Division Council.
- **0.2** Leakage of water from water fittings leads to wastage of potable water, conservation of which has become an urgent necessity. The leakage is dependent on the construction of the water fitting as well as on the quality of the washers used in the fittings. This standard lays down the requirements for the quality of washers so that they give good performance and long usage.
- **0.2.1** This standard was first published in 1967. The present revision of the standard has been taken up to incorporate changes found necessary in the standard in the light of improvements made by the industry in this field.
- 0.3 A well-manufactured washer should last at least six months and the washer fitted in taps should be replaced when signs of leakage are visible.
- **0.4** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

^{*}Rules for rounding off numerical values (revised).

IS: 4346 - 1982

1. SCOPE

1.1 This standard covers requirements of washers for water services suitable for use in bib taps, stop valves, self-closing taps, flush valves, pillar taps and ferrules covered in IS: 781-1977*, IS: 1795-1982†, IS: 1711-1970‡, IS: 2692-1978§, IS: 5869-1970||, IS: 8931-1978¶, IS: 8934-1978** and IS: 9758-1981†† respectively.

2. TERMINOLOGY

- 2.0 For the purpose of this standard, the following definitions shall apply.
- 2.1 Cold Water Water having temperature between 0° and 45°C.
- 2.2 Hot Water Water having temperature above 45°C.
- 2.3 Tap Washers Disc fitted to the washer plate of a tap or valve in such a manner that on closing the tap or valve it is brought in contact with the seating of the tap or valve and closes the orifice against further flow.
- 2.4 Vulcanized Fibre Material consisting of super-imposed layers of specially prepared paper, chemically treated, so that the laminae are virtually destroyed with the production of a homogeneous mass of converted cellulose.

3. EFFECTS ON POTABLE WATER AND METALS

- 3.1 Effect on Potable Water Material used for tap washer shall not impart any taste to water having a residual chloride content not exceeding 0.2 mg/l or have any toxic effects or foster growth of bacteria, it shall also not impart colour when exposed for a second time in normal potable water for 24 hours in a glass containing 250 ml of water at 10° and 45°C.
- 3.2 Effect on Metal The material of the washer shall not corrode the metal seating or the washer plate sufficiently to impair the performance and life of a tap or valve.

^{*}Specification for cast copper alloy screw-down bib taps and stop valves for water services (second revision).

[†]Specification for pillar taps for water supply purposes (second revision).

Specification for self closing taps (first revision).

Specification for ferrules for water services (first revision).

Specification for pillar taps for marine use.

[¶]Specification for cast copper alloy fancy bib taps for water services.

**Specification for cast copper alloy fancy pillar taps for water services.

^{††}Specification for flush valves for fittings for water closets and urinals.

4. MATERIAL

- 4.1 Material for washers shall be one of the following:
 - a) Synthetic or natural vulcanized rubber;
 - b) Vegetable tanned hydraulic leather;
 - c) Polyethylene, high density; and
 - d) Vulcanized fibre.

5, REQUIREMENTS

- 5.1 General The quality of material to be used for washers shall be such that the washer does not crack when the tap is fully closed.
- 5.2 Synthetic or Natural Vulcanized Rubber The rubber shall conform to Grade 6 of IS: 5192-1975*.
- 5.3 Vegetable Tanned Hydraulic Leather The leather shall conform to the chemical and physical requirements given in IS: 581-1976. The moisture content shall be between 15 percent and 20 percent.
- 5.4 Polyethylene High Density High density polyethylene should conform to the requirements given in IS: 7328-1974.
- 5.5 Vulcanized Fibre The material shall comply with the following requirements:

a) Tensile strength, Min

55 MPa;

b) Density, Min

1.10 g/cm3; and

c) Shear strength, Min

55 MPa.

6. DIMENSIONS

6.1 Thickness and Diameter — Washers shall be supplied to the thicknesses and diameters as given in Table 1. The variation in thickness in the case of leather washers shall not exceed \pm 5 percent.

^{*}Specification for vulcanized natural rubber based compounds (first revision).

[†]Specification for vegetable tanned hydraulic leather (second revision).

[†]Specification for high density pohyethylene materials for moulding and extrusion.

TABLE 1 DIMENSIONS OF WASHERS

(Clause 6.1)

All dimensions in millimetres.

Nominal Size of Tap/Valve	TRICKNESS OF Washer Min	DIAMETER OF WASHER			
		Internal*	External		
			Min	Max	
(1)	(2)	(3)	(4)	(5)	
8	2.5	3	14.3	14.5	
10	4.0	4	15.9	16.1	
15	4-0	5	19.0	19-3	
20	4.0	6	25.4	25.6	
25	5.0	6	33.3	33.6	
32	5∙0	7	40.1	40.6	
40	6.5	8	47.7	48·3	
50	6.5	10	63.5	6 4 ·2	

[•]A tolerance of $\frac{+0.5}{-0.0}$ mm shall be permitted.

7. MARKING

- 7.1 The identification mark and the trade-mark of the manufacturer shall be marked on the box or carton containing washers.
- 7.2 Boxes or cartons containing washers may also be marked with the ISI Certification Mark.

NOTE — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors may be obtained from the Indian Standards Institution.

(Continued from page 2)

Members

Representing

SHRI S. R. KSHIRSAGAR

National Environmental Engineering Research Institute, Nagpur

SHRI A. W. DESHPANDE (Alternale) SHRI G. A. LUHAR

Bombay Metal and Alloy Manufacturing Co Pvt Ltd, Bombay

SHRIK. RAMACHANDRAN

Public Health Engineering Department, Trivandrum Ministry of Railways, New Delhi Leader Engineering Works, Jullundur

SHRI RANJUT SINGH SHRI D. K. SEHGAL

Delhi

SHRI B. B. SIKKA (Alternate) SHRI R. K. SOMANY

Hindustan Sanitaryware & Industries Ltd. Bahadurgarh Directorate General of Supplies & Disposals, New

SHRIT. N. UBOVEJA

BUREAU OF INDIAN STANDARDS

Headquarters:			
Manak Bhavan, 9 Bahadur Shah Zafar Marg, 1	NEW DELHI 1100	02	
	Telegrams: Manal (Common to all	csans	
Regional Offices:	Te	eleph	one
Central: Manak Bhavan, 9 Bahadur Shah Zaf NEW DELHI 110002		1 01 1 13	
*Eastern : 1/14 C. I. T. Scheme VII M, V. I. Maniktola, CALCUTTA 700054	P. Road, 3	6 24	99
Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036	į	2 18 3 16 1 24	41
Southern: C, I. T. Campus, MADRAS 60011	3 ₹4	1 25 1 29	19
†Western : Manakalaya, E9 MIDC, Marol, An BOMBAY 400093	dheri (East), 63	2 92	95
Branch Offices:			
'Pushpak', Nurmohamed Shaikh Marg, Khanpu AHMADABAD 380001	•	2 63 2 63	
‡Peenya Industrial Area 1st Stage, Bangalore BANGALORE 560058	Tumkur Road (3		55
Gangotri Complex, 5th Floor, Bhadbhada Road BHOPAL 462003	d, T. T. Nagar,	6 67	16
Plot No. 82/83, Lewis Road, BHUBANESHWA 53/5, Ward No. 29, R.G. Barua Road, 5th Bye GUWAHATI 781003		5 36 3 31	
5-8-56C L, N. Gupta Marg (Nampally Station HYDERABAD 500001	Road). 2	3 10	83
R14 Yudhister Marg, C Scheme, JAIPUR 302	000 {	6 34 6 98	32
117/418 B Sarvodaya Nagar, KANPUR 20800	⁷⁵ {2	1 68 1 82	92
Patliputra Industrial Estate, PATNA 800013 T.C. No. 14/1421. University P.O., Palayam TRIVANDRUM 695035	ſ	6 23 6 21 6 21	04
Inspection Offices (With Sale Point):	1 × 1	·	••
Pushpanjali, First Floor, 205-A West High Cou Shankar Nagar Square, NAGPUR 440010	art Road,	2 5 1	71
Institution of Engineers (India) Building, 133: PUNE 411005	2 Shivaji Nagar,	5 24	35
*Sales Office in Calcutte is at 5 Chowringhee App	roach, P. O. Princeo	27 68	00

^{*}Sales Office in Calcutta is at 5 Chowringhee Approach, P. O. Princep 27 68 00 Street, Calcutta 700072

[†]Sales Office in Bombay is at Novelty Chambers, Grant Road, 89 65 28 Bombay 400007

[‡]Sales Office in Bangalore is at Unity Building, Narasimharaja Square, 22 36 71 Bangalore 560002